

MACHINERY / STRUCTURES

FINISHES

VARNISH/ENAMEL	Nozzle	Aircap	
4100 XTREME Suction	1.6 / 1.8	96 / XT01	Parts painting in general, retouches and repairs
3300 PRO Suction	1.6 / 1.8	EPA	
4100 XTREME Pressure	1.2 / 1.4	765 / XT01B	High quality painting with medium and low thickness
3300 PRO Pressure	1.2 / 1.4	EPA	
XTREME Mix/Mini Xtreme Mix	13/40 - 15/40	Xtreme	High pressure painting, maximum quality with medium/high viscosity paints
PSAM 107 / PSAM 104	13/40 - 15/40	-	



LOW/MEDIUM PRODUCTION	Applications
652 / 653	Low viscosity 1k finishes, max. 100L per working day
DM 1/300	Low viscosity finishes, continuous painting
MEDIUM/HIGH PRODUCTION	Applications
DM 1/400	Low viscosity, high air flow, continuous painting
MACK 150 Mix	Medium thickness and high speed
HIGH PRODUCTION	Applications
MACK 320 Mix	Quality painting with high speed and thickness
MACK 320 / MACK 400	Maximum speed and thickness, Airless painting

PRIMERS

PHOSPHATING/ANCHORING	Nozzle	Aircap	
4100 XTREME Suction	1.4 / 1.6	XT01	Retouches, repairs, small parts
3300 PRO Suction	1.4 / 1.6	EPA	
4100 XTREME Pressure	1.2 / 1.4	XT03 / XT01B	Complete structures and large pieces, continuous painting
3300 PRO Pressure	1.2 / 1.4	EPA	
STANDARD PRIMERS	Nozzle	Aircap	
4100 XTREME Suction	1.8	96 / XT01	Patches, repairs, parts and small surfaces
4100 XTREME Gravity	1.6 / 1.8	96 / XT01	
3300 PRO Suction	1.8	EPA	
3300 GTO Gravity	1.6 / 1.8	EPA	

PRIMERS

STANDARD PRIMERS	Nozzle	Aircap	
4100 XTREME Pressure	1.4 / 1.8	765 / XT01B	Medium/low viscosities, medium thickness and high quality finishes
3300 PRO Pressure	1.4 / 1.8	EPA	
XTREME Mix / Mini Xtreme Mix	15/40 - 18/40	Xtreme	High-pressure painting, maximum speed with medium/high viscosity
PSAM 107 / PSAM 104	15/40 - 25/40	-	
HIGH VISCOSITY PRIMERS	Nozzle	Aircap	
4100 Gravity	2.2 / 2.8	64S / 62S	Parts and panels painting with medium and high thickness
3300 GTO Gravity	2.2 / 2.8	64S / 62S	
4100 XTREME Pressure	1.8	765 / XT01B	
3300 PRO Pressure	1.8	EPA	
XTREME Mix / Mini Xtreme Mix	18/40	Xtreme	High-pressure painting, maximum speed and productivity
PSAM 107 / PSAM 104	18/40 - 25/40	-	



LOW/MEDIUM PRODUCTION	Applications
6110 / 610	Occasional use, parts or series, repairs
652 / 653	Daily use, paint volumes up to 50 L
HIGH PRODUCTION	Applications
DM 1/300 - DM 1/400	Continuous painted with low/medium viscosities
MACK 320 Mix/MACK 320	High thickness with medium/high viscosity
MACK 400	Maximum speed of application with high viscosity

HIGH THICKNESS PRIMERS	Nozzle	Aircap	
PSAM 107	21/32	-	High pressure painting, high thickness and viscosity
MACK 400 / MACK 600	High pressure and flow in airless aplic.		

AIR CONDITIONING

FINISHES	Applications
4120	Mechanical filtering of solid particles (20u), water and oil
479 Plus	Mechanical filtering of solid particles (40u), water and oil
PRIMERS	Applications
479 Plus	Mechanical filtering of solid particles (40u), water and oil
439 Plus	Inline filtering up to 40u

